


## P SERIES. especial

FIRE HOSE REEL WITH **SUPPORT BASE** 

## Model: 25/20/25/30 P SB .

Fire Hose Reel with manual stop valve. The Fire Hose Reel is mounted on a support base which is fixed to the groud. The water supply piping can be hidden inside the metalic support structure.





## technical features

Model	25/20 P SB, 25/25 P SB and 25/30 P SB		
Certificate	According to EN 671-1:2012		
Fire Hose Reel	Steel side discs of Ø550mm - 1,2 mm		
	Centre parts made of brass		
	Fixed on the support base		
	1,10 mt supply hose including spiral spring		
	Corrosion treatment		
	Electrostatic powder painting - min. 70 mícron		
Support base	Galvanized steel St12 - 1,5mm		
	Dimensions: (W)300 x (H)1300 x (D) 100mm		
Hose	Ø 25mm, according to EN 694		
Nozzle	Three positions (Shift-off / jet / spray)		
	Ø 10mm   Factor K = 42		
Stop valve	1" manual stop valve		

MODEL	HOSE		DIMENSIONS	REFERENCE
	Ø	Lingth	WxHxD	REFERENCE
25/20 P SB	25mm	20m	550 x 1500 x 245mm	301044
25/25 P SB	25mm	25m	550 x 1500 x 245mm	301099
25/30 P SB	25mm	30m	550 x 1500 x 285mm	301081

OPTIONS:

Pressure gauge: 0 – 25 bar



