




STAINLESS STEEL FIRE HOSE REEL

Model: 25/20/25/30 P (T180°) AICN =

Stainless Fire Hose Reel equipped with a manual stop valve. The Fire Hose Reel is supplied with a wallmouting swinging arm, allowing the hose reel to swing through 180°, enabling the hose to run in all directions.



tec	hni	ical	l fea:	ures

10011111001	10 01 01 00				
Models	25/20 P (T180°) AICN, 25/25 P (T180°) AICN and 25/30 P (T180°) AICN				
Certificate	According to EN 671-1:2012				
Fire Hose Reel	Stainless steel side discs Ø550mm - 1,2 mm				
	Centre parts made of brass				
	Swinging arm support - Swinging angle of 180°				
	1,10 mt supply hose including spiral spring				
Hose	Ø 25mm, according to EN 694				
Nozzle	Three positions (Shift-off / jet / spray)				
	Ø 10mm Factor K = 42				
Stop valve	alve 1" manual stop valve				





MODEL		HOSE		DIMENSIONS	REFERENCE
	WODEL	Ø	Length	Ø x W x D	REFERENCE
	25/20 P (T180°) AICN	25mm	20m	550 x 650 x 200mm	
	25/25 P (T180°) AICN	25mm	25m	550 x 650 x 200mm	
	25/30 (P T180°) AICN	25mm	30m	550 x 650 x 240mm	301165.I

OPTIONS:

Pressure gauge: Hose:

0 – 25 bar Textile coating

